



## Highlights:

- · Multi-tapping 100V line transformer
- Multi-functional wall bracket allowing swiveling and downtilting
- · Slimline aluminum design
- 12 x 2" high-quality broadband speakers


#### Product information:

The KYRA12 design column speaker consists of 12 x 2" high-quality aluminum cone full-range drivers, delivering extraordinary clarity and detailed sound. The overall continuous power handling reaches 120 Watt and the beamwidth of 170° x 20° makes it the perfect match for acoustically difficult venues, reducing echo and microphone feedback which optimizes the speech intelligibility in reverberant venues.

A multi-tapping line transformer allows it to be connected to 70V/100V public address systems with different power taps for 40W, 20W and 10W and/or low impedance (12 $\Omega$ ) systems.

### Applications:

- Education
- · Public facilities
- · Corporate spaces
- · Houses of worship
- Events



# System specifications:

Speaker type		Broadband column
Max. Power		240 W
RMS Power		120 W
Impedance		12 Ω
Sensitivity (1W/1m)		92 dB
Sound Pressure (Max. W/1m)		113 dB
Frequency	Range (-10 dB)	120 Hz - 20 kHz
	Response (± 3 dB)	150 Hz - 20 kHz
Drivers		12 x 2"
Line Transformer Tappings	1	40 W - 125 Ω (70V)
	2	250 Ω - 100 V / 40 W - 70 V / 20 W
	3	500 Ω - 100 V / 20 W - 70 V / 10 W
	4	1000 Ω - 100 V / 10 W - 70 V / 5 W
Ingress Protection rating		IP3x
Temperature	Operating	-20 - +50 °C
Incline angle	Left	42°
	Right	42°
	Bottom	13°
Dispersion	Horizontal	260° (-6 dB average 100 Hz – 10 kHz)
	Vertical	90° (-6 dB average 100 Hz – 10 kHz)

### **Product Features:**

Front finish		Steel grill
Construction		Aluminium with plastic side covers
Dimensions		70 x 1006 x 101 mm (W x H x D)
Colours		Black (KYRA12/B - RAL9005)
		White (KYRA12/W - RAL9003)
Accessories	Included	2-way Revolving mounting bracket
		1 x 3-pin Euro Terminal Block Input connectors

### Variants:

- KYRA12/B Black version
- KYRA12/W White version

### Horizontal Polars:

