

VIRO5 Compact performance loudspeaker

Highlights:

- · Warm & true to nature sound
- · Weatherproof IP55 rating
- · Countless mounting possibilities
- · Diverse connections possibilities
- · High grade aluminum construction
- · 70V/100V transformer option available

Product information:

"A sound that lasts"

The VIRO is a powerful 2-way performance speaker which is designed for outdoor and indoor use, ensuring true-to-nature, high fidelity reproduction of music and speech in every environment, ranging from residential applications to the most demanding outdoor applications in parks, hotels and even clubs.

Crafted in high-grade aluminium with incredible attention to detail. The material choice goes well beyond aesthetics. It also provides superior acoustic properties thanks to its material stiffness and seamless surfaces that eliminate any distortion of your sound.

The aluminium construction and grill with hydrophobic cloth provides the necessary protection for all weather conditions. The combination of the cloth, sealing rubbers and drainage holes on the bottom of the speaker make it IP55 compliant.

Exchange your connections easily. From cable glands with rubber grommets to optional SpeakON connections and even an optional 70/100V transformer (TRV106).





Certification:



Properties:



Impedance:



Voltage:

System specifications:

| Speaker type | | Compact performance 2-way coaxial |
|----------------------------|----|-----------------------------------|
| Peak power handling | | 240 W |
| Program power handling | | 120 W |
| RMS/AES power handling | | 60 W |
| Impedance | | 8 Ω (VIRO5) |
| | | 16 Ω (VIRO5D) |
| Sensitivity (1W/1m) | | 89 dB |
| Sound Pressure (Max. W/1m) | | 110 dB |
| Dispersion | | 225° |
| Drivers | HF | Soft dome treated silk 1" |
| | LF | 5 1/4" Treated paper |
| Connectors | | 4-pin Euro Terminal Block |
| Ingress Protection rating | | IP55 |
| Outdoor resistance | | 720 hrs salt spray test |

Product Features:

| Dimensions | | 198 x 135 x 191 mm (W x H x D) (Incl. bracket) |
|---------------------|------------------|--|
| | | 180 x 180 x 191 mm (W x H x D) (Excl. bracket) |
| Mounting | Mounting pattern | 40×70 mm mounting pattern (e.g. pole or ground pin fitting) |
| Mounting & handling | Stand fitting | 3/8" stand fitting (microphone stand) |
| Construction | | Textured powder coated aluminium 4 mm |
| Front finish | | Aluminium grill with hydrophobic cloth |
| Colours | | White (RAL9003) (VIRO5/W & VIRO5D/W) |
| | | Black (RAL9005) (VIRO5/B & VIRO5D/B) |
| Weight | | 4.2 kg |
| Accessories | Included | Mounting bracket |
| | Optional | TRV106 70-100V transformer module |
| | | CVS102 SpeakON connection plate |
| | | MBK523/G Ground pin |
| | | MBK530 Pole mount |
| | | STG601 Steel drop safety wire (gripple) |

Variants:

- VIRO5/B Black version 8Ω
- VIRO5/W White version 8Ω
- VIRO5D/B Black version 16Ω
- VIRO5D/W White version 16Ω

Horizontal Polars:

