

Highlights:

- Standard keylock for both doors
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 940 mm)
- Tempered glass door with keylock
- Reversible door position
- Stores up to 42 units of 19" equipment

Product information:

The SPR1042 is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provides a solid and stable construction making it suitable for heavy equipment, storing up to 42 units inside. The SPR1042 comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and leveling once correctly positioned.

The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19" profiles provide great flexibility for installing equipment depending on its depth. Both front and rear doors are fitted with a standard keylock.



Product Features:

Unit height		42 HE
Weight		120 kg
Colours		Black (RAL9004)
Max. usable depth		940 mm
Wheel	Diameter	50 mm
Dimensions		600 x 1985 (2055) x 1000 mm (W x H (incl. feet) x D)
Static load capacity (adjustable feet)		800 kg
Dynamic load capacity (transport castors)		400 kg
Accessories	Included	4 x Key for sidepanel lock
		1 x Allen key
		4 x Levelling feet
		4 x Key for front/back door
		20 x KS600
		20 x KM600
	Optional	KM600 - M6 Cage nuts
		KS600 - M6 x 16 mm bolt DIN7985 Black
		SPR10CS - Rack interconnection slot
		SPR100LR
		SPR100PT
		SPR100RF

