


Highlights:

- Stores up to 42 units of 19" Equipment
- Width of 800 mm for convenient installation and maintenance
- Available space on sides for cable management systems and accessories
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 740 mm)
- Reversible door position
- Mesh perforation with hexagonal pattern
- Swing handle with cylinder lock

The SPR8842GG is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provide a solid and stable construction making it suitable for heavy equipment, storing up to 42 units inside. The SPR8842GG comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and levelling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19" profiles provide great flexibility for installing equipment depending on its depth.

The SPR8842GG comes with 2 perforated steel grill doors (front and rear). The mesh perforation with hexagonal pattern provides an optimal air flow through the cabinet. The swing handle with cylinder lock safely locks the equipment inside. The width of 800 mm offers additional space for the installation of accessories and cable management systems, while guaranteeing an optimal convenience for installation and maintenance of the equipment.



Product Features:

Unit height		42 HE
Colours		Black (RAL9004)
Max. usable depth		740 mm
Wheel	Diameter	50 mm
Dimensions		800 x 1985 (2055) x 800 mm (W x H (incl. feet) x D)
Accessories	Included	4 x Key for sidepanel lock
		1 x Allen key
		4 x Levelling feet
		4 x Key for front/back door
		20 x KS600
		20 x KM600