

Highlights:

- Stores up to 6 units of 19" Equipment
- Punched square holes for use with snap-in cage nuts
- 2.0 mm thick cold rolled steel frame
- Easy assembly in 5 minutes
- Ships as flat-down package
- Desktop standing use
- Slanted front for optimal stability and equipment viewing
- Perforated sides for cable guiding or accessories mounting

The TPR306 is a professional and solid constructed desktop rack for 19" equipment compliant to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. It ensures maximum installation, connectivity and maintenance ease storing up to 6 units for studio, processing, test and other 19" equipment. The slanted front profiles offer optimal stability and a perfect viewing angle to the front panels of the equipment. The construction is made of 2.0 mm thick steel finished in a black (RAL9004) powder coating with fine structure. Punched equipment mounting profiles on the front offer a multifunctional use of the rack while perforated sides allow cable guiding or accessories mounting. Delivered in a flat-down package, the simple structure allows assembly by a single person in record-breaking time.



Product Features:

Unit height	6 HE
Max. load	30 kg
Dimensions	504 x 316 x 294 mm (W x H x D) (excl. rubber feet)
Weight	2.5 kg
Colours	Black (RAL9004)
Accessories	Included 1 set Assembly hardware 24 x Cage nuts + screws

Architects' and Engineers' Specifications:

The rack shall be a 19" desktop rack which complies to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards with 6 usable rackspaces. It shall have the following dimensions: height 316 mm, width 504 mm and depth 294 mm with a weight of 2.5 kg. The frame of the rack shall be constructed out of cold rolled steel with a thickness of 2.0 mm. Punched square holes for use with snap-in cage nuts shall be provided for fixation of the equipment, while perforated sides shall allow easy cable guiding or accessories mounting. Slanted front profiles shall offer an optimal stability and viewing angle to the front panels of the equipment. The finishing shall be done in a textured black powder coating (RAL9004) color and have printed unit measurement indicators. The rack shall ship unassembled as a flat-down package and provide a static load capacity of 60 kg.

